

# Leica Zeno GG04 plus

## Data sheet



### Smart device independence

Using the Zeno GG04 plus smart antenna with your controller from Leica or own device is simple, regardless if it runs on Android™, iOS or Windows® platforms. Now you can feel right at home while carrying out your data collection tasks. Bluetooth® connectivity ensures cable free operation and high accuracy configuration is easy with just a few clicks in the Zeno Connect application.



### Precise Point Positioning (PPP)

PPP enables the GG04 plus to achieve high accuracy data collection without the need for a mobile data connection. PPP works by using a satellite based correction service to broadcast data directly to the GG04 plus. Corrected data is processed onboard the antenna and delivered seamlessly to your device. PPP is available anywhere in the world at any time.



### Extensive software support

Not only will the Zeno GG04 plus smart antenna work with Zeno Mobile and Zeno Field software, but, with the help of Zeno Connect it will also work with other data collection apps and software. No development efforts are required to achieve centimetre accurate positioning. If required GNSS metadata can be queried additionally.



[leica-geosystems.com](http://leica-geosystems.com)



- when it has to be **right**

**Leica**  
Geosystems

# Technical Specifications

## LEICA ZENO GG04 PLUS | GNSS TECHNOLOGY

Number of channels	555 channels (more signals, fast acquisition, high sensitivity)	
Satellite signal tracking	GPS (L1, L2, L2C/L2P, L5), Glonass (L1, L2, L3), BeiDou (B1, B2, B3 <sup>1</sup> ), Galileo (E1, E5a, E5b, Alt-BOC, E6 <sup>2</sup> ), QZSS, NavIC (IRNSS, L5), SBAS (WAAS, EGNOS, MSAS, GAGAN), L-band	
Real-time and post-processing	Support of real-time correction service and post-processing to achieve positioning accuracy	
Output data protocols	<ul style="list-style-type: none"> <li>Windows<sup>®</sup>: NMEA<sup>2</sup> via Zeno Connect</li> <li>Android: position provided by Location Service and NMEA<sup>2</sup> output possible, both via Zeno Connect</li> <li>iOS: position provided by iOS Location Feature and NMEA<sup>2</sup> output possible (via EA protocol) via Zeno Connect</li> </ul>	
Update rate	20 Hz (0.05 sec) <sup>3</sup>	
Post-processing accuracy static mode	Horizontal: 3 mm + 0.5 ppm (rms) <sup>4</sup> Vertical: 6 mm + 0.5 ppm (rms) <sup>4</sup>	
Horizontal real-time accuracy (SBAS or external source)	SBAS, L1 only	< 0.9 m <sup>4</sup>
	Spot Lite, PPP (Multi-frequency option needed)	< 60 cm <sup>4</sup> after approximately 8 minutes of converging
	DGNSS, L1 only	< 40 cm <sup>4</sup>
	Spot Prime, PPP (Multi-frequency option needed)	< 10 cm <sup>4</sup> after approximately 15 minutes of converging
	RTK, Multi-frequency	< 1 cm + 1 ppm <sup>4</sup>
Vertical real-time accuracy	RTK (Multi-frequency): 2 cm + 1 ppm <sup>4</sup>	
Real-time protocols	RTCM 2.x, RTCM 3.0, RTCM 3.1, RTCM 3.2, RTCM MSM, CMR, CMR+	
Integrated real-time	SBAS <sup>5</sup> (EGNOS, WAAS, MSAS, GAGAN), or PPP via L-band (requires a valid Spot option)	
Time for initialisation	Typically 6 sec <sup>6</sup>	

## INTERFACE & COMMUNICATION

User interface	On/Off key Status indicator (LED): satellite tracking, Bluetooth <sup>®</sup> communication and battery power
Communication port	Bluetooth <sup>®</sup> 4.1 class 1 & sealed and protected 8-pin Lemo combined USB / Serial232 port
Field controller connection	By Bluetooth <sup>®</sup> (3 ports available), RS232 or USB cable

## POWER MANAGEMENT

Removable battery	GEB212 (7.4 V / 2600 mAh Li-Ion rechargeable)
Battery charging time	2 hours to full charge with GKL341
Power	Nominal 12 V DC Range 10.5 – 28 V DC
Operating time	7.5 h (RTK) <sup>7</sup> , 10 h (GNSS only) <sup>7</sup>

## PHYSICAL SPECIFICATIONS

Weight and dimensions	0.8 kg with all-day battery Height: 0.071 m x Diameter: 0.186 m
Proof against water, sand and dust	IP66 & IP68 (IEC60529): dust and water-resistant for all conditions: Temporary submersion into water (2 hours in 1.40 m depth) and protected against blowing rain and dust
Operating / Storage temperature range	Operation: -40 to 65 °C (-40°F to +149°F) (ISO 9022-10-08, MIL-STD-810G CHG1 Method 502.6-II & ISO 9022-11-04, MIL-STD-810G CHG1 Method 501.6-I) Storage: -40 to 80 °C (-40°F to +176°F) (ISO 9022-10-08, MIL-STD-810G CHG1 Method 502.6-I & ISO 9022-11-06, MIL-STD-810G CHG1 Method 501.6-I)
Humidity	100% (ISO9022-12-04, ISO9022-13-06, ISO9022-16-02, MIL-STD-810G CHG1 Method 507.6-I)
Drop	Withstands topple over from a 2 m survey pole onto hard surface Withstands 1 m drop onto hard surface
Vibration	Withstands strong vibration (ISO9022-36-05)

## ACCESSORIES & OPTIONAL FEATURES

Accessories	<ul style="list-style-type: none"> <li>External battery charger</li> <li>Backpack kit</li> <li>Hard carry case</li> <li>2 meter range pole</li> <li>Universal pole mounts for different sized 3rd party mobile devices</li> </ul>
Optional field and office software	<ul style="list-style-type: none"> <li>Leica Zeno Field</li> <li>Leica Zeno Mobile</li> <li>Leica Zeno Connect</li> <li>Leica Zeno Office and Leica Zeno Office on ArcGIS</li> </ul>
Optional field computers	<ul style="list-style-type: none"> <li>Leica Zeno 5</li> <li>Leica Zeno Tab Android tablet</li> </ul> or with the following 3rd party HW in combination with Leica Zeno Connect and Zeno Mobile (Android only): <ul style="list-style-type: none"> <li>Android: most phones and tablets with Android version &gt; 4.1</li> <li>Windows<sup>®</sup>: tablets/pcs/handhelds with Windows<sup>®</sup> 10/8/7 or WEH</li> <li>Apple phones and tablets</li> </ul>

<sup>1</sup> Believe to comply, but subject to availability of BeiDou ICD and Galileo commercial service definition. BeiDou B3 and Galileo E6 will be provided through future firmware upgrade.

<sup>2</sup> Supported NMEA-0183 messages: GGA, VTG, GLL, GSA, GGG, GSV, RMC, LLQ (Windows<sup>®</sup> only), GST

<sup>3</sup> 20 Hz supported for selected NMEA messages on Windows<sup>®</sup> only.

<sup>4</sup> Measurement precision, accuracy and reliability depends upon various factors including number of available satellites, geometry proximity to base station, multipath effects, ionospheric conditions, etc.

<sup>5</sup> WAAS available in North America only, EGNOS available in Europe only, MSAS available in Japan only, GAGAN available in India only.

<sup>6</sup> May vary due to atmospheric conditions, multipath, obstructions, signal geometry and number of tracked satellites.

<sup>7</sup> May vary with temperature, battery age, usage etc.

Support of different iOS and Android versions cannot be guaranteed at all times as operating system updates are out of Leica Geosystems control. Leica Geosystems publishes a list of fully tested and verified operating system versions on the customer information portal myWorld.

Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland – 2017.  
Leica Geosystems AG is part of Hexagon AB. 867461en - 07.19



The Bluetooth<sup>®</sup> word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license.

Microsoft, Windows<sup>®</sup> and the Windows logo are either registered trademarks or trademarks of Microsoft Corporation in the United States and / or other countries. Other trademark and trade names are those of their respective owners.

Apple, iPad, iPad Air, iPad Pro, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries.

Android<sup>™</sup> is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Use of the Made for Apple badge means that an accessory has been designed to connect specifically to the Apple product(s) identified in the badge, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.

**Leica Geosystems AG**  
Heinrich-Wild-Strasse  
9435 Heerbrugg, Switzerland  
+41 71 727 31 31

- when it has to be **right**

