

Product Data Sheet: FlatMesh PT100 RTD Sensor Node

The FlatMesh PT100 RTD Sensor Node allows precision temperature sensing in many different situations. It uses the integrated mesh radio transceiver to report its measurements through Senceive's FlatMesh wireless communications network to a FlatMesh Gateway.



Temperature monitoring applications:

- Steel structures
- Rail, for critical rail temperature alerting
- Concrete structures, including during curing
- Heating, Ventilation, and Air Conditioning (HVAC) systems
- Ambient/environment

Key Features

- Waterproof, robust connectors for simple installation
- Accuracy of $\pm 0.1^{\circ}\text{C}$
- Can have an integrated triaxial tilt sensor for combined tilt and temperature sensing in one unit •
Integrated long life battery
- 12-15 year battery life, including when acting as a relay node within the mesh communications network
- Versatile mounting options
- Waterproof to IP66 / IP67 / IP68
- Firmware is remotely upgradeable over the air via the gateway reducing costly site visits
- Easily deployed

Channel Combinations

Model	Ports	Applications
FM3N-RTD	1 PT100 RTD Channel	Single point temperature monitoring

FM3N-IX-RTD	1 PT100 RTD Channel 1 Integrated high precision triaxial tilt sensor	Structural monitoring with precision temperature compensation Railway deformation and critical rail temperature monitoring
FM3N-IXH-RTD	1 PT100 RTD Channel 1 Integrated high precision high-g triaxial tilt sensor	Structural monitoring with precision temperature compensation Railway deformation and critical rail temperature monitoring

Physical Specifications

Parameter	Value
Dimensions excluding antenna and vent	90 x 90 x 60 mm
Dimensions excluding antenna	90 x 96 x 60 mm
Total Mass	0.57kg
Housing Material	Die cast aluminium
Protection (BS EN 60529: 1992 + A2: 2013)	IP66 / IP67 IP68 at 1m for 24 hours
Mounting Options	M4 blind holes in side ¼" UNF holes in bottom
Operating Temperature Range	-40°C to +85°C

FlatMesh Radio Specifications

Parameter	Value
Communication Type	Proprietary FlatMesh v3 Mesh Networking Protocols IEEE 802.15.4 compliant
Frequency Band	2400 – 2485 MHz ISM Band
Maximum Transmit Power (EN 300 328 v1.8.1)	6.5dBm
Maximum Permitted Antenna Gain	2.2dBi
Range	Up to 300m depending on the environment and fitted antenna Consult with Senceive for your application
RF Module	Senceive FM3Node

RTD Interface

Parameter	Value
Connector	M12 Female 5-pole A-coded Screw-in Type
Accuracy	±0.1°C
Resolution	0.01°C
Stimulus Type	Constant Current

Tilt Sensor (-IX, -IXH variants only)

Parameter	Value
Resolution	0.0001° (0.00175mm/m)
Repeatability (-IX variant)	±0.0005° (0.0087mm/m)
Repeatability (-IXH variant)	±0.0025° (0.0436mm/m)
Range	±90°

Internal Battery

Parameter	Value
Battery Type	Lithium Thionyl Chloride
Nominal Voltage	3.6V
Nominal Capacity	19000mAh
Typical Battery Life	12-15 years at 20/30 minute reporting intervals, including when acting as a relay node Consult with Senceive for your application

Certifications

- Tested to conformity with all the essential requirements of RED Directive 2014/53/EU and RoHS Directive 2011/65/EU
- FCC Grant of Equipment Authorization: FCC ID 2AMFBFM3N
- Network Rail Acceptance PA05/04146
- London Underground Approved

Ordering Information and Accessories

Model	Description
FM3N-RTD	FlatMesh 3 PT100 RTD Sensor Node
FM3N-IX-RTD	FlatMesh 3 Triaxial Tilt Sensor and PT100 Sensor Node
FM3N-IXH-RTD	FlatMesh 3 Triaxial High-g Tilt Sensor and PT100 Sensor Node
FS-PT100R-xxxxx	Round Bead Temperature Sensor For fluid temperature (and air temperature) sensing or for drilled holes xxxxx is the cable length in millimetres
FS-PT100S-xxxxx	Surface Mount Temperature Sensor Metal leaf can be glued or spot welded to a surface xxxxx is the cable length in millimetres
FS-PT100M-xxxxx	Magnetic Temperature Sensor Surface temperature of metal structures xxxxx is the cable length in millimetres
FF-MP-S360	Swivel mounting kit with 360-degree adjustment range - screw directly to vertical walls

FF-MP-V	Vertical mounting plate <ul style="list-style-type: none"> - use U-bolts to fix to poles or stakes - use glue to fix to walls where drilling is not permitted Use with FF-MP-S360
FF-MP-H	Horizontal mounting plate - screws to brick/concrete
FF-MP-HM	Horizontal magnetic mounting plate
FF-MP-RA	Right angle mounting bracket <ul style="list-style-type: none"> - screw to concrete tunnel linings and inclined walls Use with FF-MP-S360
FF-MP-T2	Track bed mounting plate kit
FF-MP-M2	Magnetic mounting kit High degree of adjustability, perfect for cast iron lined tunnels
FF-BK-xxxx FF-BE	Tilt beam kit See separate datasheet for more information
FA-FM-WPS	Waterproof straight antenna Overall node height 168mm (approx.) when fitted Maximum gain +1.1dBi
FA-FM-LPS	Waterproof low profile straight antenna Minimum overall node height, perfect for track bed and tight spots Overall node height 92mm (approx.) when fitted Maximum gain 0dBi
FA-FM-ADJ	Adjustable angle antenna Flexible installation, perfect for use in tunnels and indoor environments Overall node height 202mm (approx.) when upright Overall node height 102mm (approx.) when at 90-degree angle Maximum gain +2dBi
FC-NC	Antenna cover kit Use with FA-FM-LPS antenna Overall node height 96mm (approx.) when fitted