



# **R4: TECHNICAL**

#### **General Technical Data**

Power Supply	12-32 V
Operating Temperature	-20°C to +50°C
Weight	1,400 g
Overall power consumption	10 W
Sensor tube dimensions (L x D)	2,074 x 29 mm

### FGM3D/75 Fluxgate

Number and orientation of sensors	5 sensors, laid horizontal, parallel
Specified measurement range	±75,000 nT (other ranges on request)
Number of sensor axis	3
Distance between sensors	500 mm
Noise level @1Hz [pT/ (Hz)]	10 pT < all sensors M1-M5 < 20 pT

## **Datalogger**

Power	50 mA
Sensor input	Hard wired, 50cm sensor cable
User Interface	Start/Stop button; Webserver
Survey mode	Continuous recording while airborne
Sampling rate	200 – 1000 Hz
Internal memory	32 GB (approx. 500h+ recording with 200Hz)
Datalogger dimensions (W x D x H)	264,5 x 104,5 x 80 mm

## **Data Processing**

MagDrone DataTool (included)	Raw data filtering, track & flight direction detection, noise compensation, MagBase or GPS referencing, export, preview
MAGNETO® Software	Data interpretation, visualization, object calculation, etc.
Live output	Via Ethernet interface

#### **GPS Add-on**

EMITE M2 / DC2	Interface for EMLID M2 multiband RTK GPS
EMLID M2 / RS2	with optional EMLID RS2 base station

UAV / drone magnetometer survey kit

# **MAGDRONE R4**





#### **Applications**

- ➤ Survey & Surveillance
- Mine exploration / tracking / monitoring at flexible heights
- UXO detection on unreachable, flooded or mined areas

#### **Features**

- Dismountable system with 5 Fluxgate sensors
- > Attachable to any UAV with 1.5+ kg payload
- > Made for DJI M300
- > 8 GB internal memory
- ➤ 200 Hz recording rate
- Data loss prevention
- > WLAN interface
- Data processing tool

The MagDrone R4 is an ultra light weight magnetometer survey kit with 5 triaxial Fluxgates to be attached to any UAV with a 1,400 g payload. Its dismountable sensor tube allows for sensor spacing of either 25cm or 50cm providing a 2.5m swath width.

With 200Hz sampling rate the R4 can easily filter out noise from infrastructure, net frequencies or UAV motors. Hence, it can be directly installed on UAV's landing gear for a very compact setup. The MagDrone R4 can be used for i.e. magnetic cartographies, mine exploration, area scanning for bombs and ammunition (UXO), preventive check and surveillance of areas and camps against intrusion.

The MagDrone Data Tool identifies flown tracks, cut, filter, compensate the raw data, generates a preview and exports into various formats to further process the recorded values, i.e. with our MAGNETO®.





# **R4: ALL UNIQUE SELLING POINTS AT HAND**

# Your benefits with our solution

### ✓ Universal usage

- UXO Search
- Exploration
- Surveillance
- ✓ **Ideal for DJI M300/M350**With 1,500g, the R4 gets on board any professional UAV easily, but especially the DJI M300/M350!
- ✓ **Straight interface**Access the R4 via WLAN for configuration or start/stop triggers.
- ✓ **Most simple installation**Take 4 cable ties and strap it on your UAV landing gear.

## √ 1-button operation

You can't go wrong – the R4 has only one button to make operation as simple as possible!

#### √ Noise cancellation

Due to a high sampling rate, UAV motor noise is accepted, detected and can be filtered out during raw data export.

#### ✓ Powerful DataTool

The free MagDrone DataTool lets you delete tracks, compensate, filter, ... and allows various exports!

# Most frequent questions

### What can it detect?

The magnetometers detect everything ferrous (iron) – but i.e. not Aluminum or Gold as they are conductive only.

## How deep can it sense?

It depends. The R4 sees a harvester machine from 40m distance; but a hand grenade from only a few centimeters.

## Ideal flight height?

For compact objects: as close as possible – 50cm above ground. Can be dozen of meters for soil structures.

## Does it work over water?

Yes. Water doesn't affect sensor operation or damping the magnetic field strength (to be detected).

### > Sensitivity of the sensors

The sensitivity of the installed FGM3D/75 is  $0.13V/\mu T$ , the resolution is better than 150pT.

#### Interference from UAV

Constant noise (motors) is ok and is filtered out, but don't use a camera gimbal with the R4.

# **R4: DATALOGGER INSTALLATION**



